

Kuriyama of America, Inc.

Industrial Hose & Couplings For Septic, Wastewater & Irrigation

Featuring Products by Tigerflex™, Alfagomma®, Piranha® & **KOA Couplings & Accessories™**







Headquarters, Sales Office and Warehouse Location

360 E. State Parkway, Schaumburg, IL 60173-5335

Phone: (847) 755-0360 • Toll-free Fax: (800) 800-0320 • International Fax: (847) 885-0996 Web Site: www.kuriyama.com • E-Mail: sales@kuriyama.com

www.kuriyama.com on the Web

CONTACT OUR SALES/WAREHOUSE LOCATIONS BELOW WHICH SERVE YOUR AREA

SOUTHWEST WAREHOUSE KURIYAMA OF AMERICA, INC. HOUSTON

200 Portwall St., Suite 100 Houston, TX 77029 Phone: (713) 674-8212 Toll Free Phone: (800) 501-6808 Fax: (562) 941-8940 Fax: (713) 674-5214 Toll Free Fax: (800) 800-5214

WESTERN WAREHOUSE KURIYAMA OF AMERICA, INC. **SANTA FE SPRINGS**

10749 Shoemaker Ave. Santa Fe Springs, CA 90670-4039 Phone: (562) 941-4507 Toll-Free Fax: (800) 326-8940

SOUTHEAST WARFHOUSE FORTNEY SALES CO., INC. 4221 Cantrell Road NW Acworth, GA 30101 Phone: (770) 427-6528 Fax: (770) 423-9249 Toll Free Fax: (800) 423-9249 Web Site: www.fortneysales.com

E-Mail: sales@Ffortneysales.com

FASTERN WAREHOUSE EASTERN RUBBER & PLASTICS

100 Goldman Dr. Plumsted Industrial Park Cream Ridge, NJ 08514 Phone: (609) 758-0100 Fax: (609) 758-0102 Toll Free Fax: (800) 445-7138 Web Site: www.easternrubber.com E-Mail: sales@easternrubber.com

KURI TEC CORPORATION Box 21052, L P M P 0 140 Roy Boulevard Brantford, Ont, Canada N3r 7W9 Phone: (519) 753-6717 Fax: (519) 753-7737

Web Site: www.kuritec.com E-Mail: sales@kuritec.com

KURIYAMA DE MEXICO S DE RL DE CV Av Jose Palomo Martínez No 520-20 Bodega 5 Parque Industrial Omolap Apodaca, N.L. CP: 66633, México Telefonos (81)1086-1870 ó 1086-1871 Lada sin Costo 01 800 822 52 00

Correo Electronico: ventas@kuriyama.com

Internet: www.kuriyama.com

The trademarks contained in this publication are trademarks of Kuriyama of America, Inc. The "Alfagomma" trademark contained in this publication is a registered trademark of Alfagomma S.p.A. The "Tigerflex" design trademarks contained in this publication are trademarks of Tigers Polymer Corporation.





Septic and Wastewater Hoses

Tiger™ Green TG™ Series

EPDM Suction Hose

Tiger™ Yellow TY™ Series

EPDM Suction Hose

Tiger™ Red **TRED™** Series

EPDM Suction Hose

Tiger™ Blue **TBLU™** Series

EPDM Suction Hose



GENERAL APPLICATIONS:

Agriculture liquid fertilizers Irrigation lines Liquid manure handling Marine bilge discharge Pumps, rental and construction dewatering Pumps, trash Septic and wastewater handling Water suction - standard duty



EPDM tube with polyethylene helix.

SERVICE TEMPERATURE:

-40°F (-40°C) to 160°F (+71°C)



AVAILABLE SIZES:

	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	6"
TG™	Х	Х	Х	Х	Х	Χ	Х	Х
ТҮтм	Х	Х	Х	Х		Х	Х	
TRED™				Χ		Χ	Χ	
TBLU™				Х		Х	Х	

KBEE™ Series

Polyethylene Liquid Suction and Wasterwater Hose MADE IN THE







GENERAL APPLICATIONS:

Pumps, rental and construction dewatering Pumps, trash Septic and wastewater handling Water suction - standard duty

CONSTRUCTION:

Flexible polyethylene (LDPE) tube with polyethylene (LDPE) ribs and cuffed ends.

SERVICE TEMPERATURE:

-40°F (-40°C) to 150°F (+65°C)



AVAILABLE SIZES:

	2"	3"
КВЕЕ™	Χ	Χ

Tiger™ TSD™ Series

EPDM Fabric Reinforced Suction & Discharge Hose MADE IN THE USA



GENERAL APPLICATIONS:

Agriculture liquid fertilizers Agri-foam systems Liquid manure handling Pumps, rental and construction dewatering Pumps, trash Septic and wastewater handling Suction and discharge Water suction - heavy duty

CONSTRUCTION:

Double-ply EPDM, polyester fabric reinforcement and polyethylene helix.

SERVICE TEMPERATURE:

-40°F (-40°C) to 160°F (+71°C)

AVAILABLE SIZES:

	1"	1-1/4"	1-1/2"	2"	3"
TSD™	Х	Х	Х	Х	Х

KSWBR0218



Vac Truck Hydroexcavation and Trenching Hoses

Tiger™ TR1™ Series Heavy Duty SBR Wet or Dry Material Handling Hose





AVAII ARI F SIZES:

		1441	LADI	3		<u>. </u>		
	1-1/2"	2"	2-1/2"	3"	4"	5"	6"	8"
TR1™	Х	Х	Х	Х	Х	Х	Х	Х

GENERAL APPLICATIONS:

Fly ash collection Hydro excavation Industrial vacuum equipment Material handling - heavy duty abrasive Milling machine scrap recovery Rock, gravel, sand and crushed concrete vacuuming Sewer truck boom hose Shot blast recovery Slurry handling



CONSTRUCTION:

SBR rubber tube with rigid PVC helix.

SERVICE TEMPERATURE:

-40°F (-40°C) to 150°F (+65°C)

Amphibian™ AMPH™ Series

Heavy Duty Polyurethane Lined Wet or Dry Material Handling Hose MADE IN THE



AVAILABLE SIZES:

	4"	5"	6"	8"
AMPH™	Χ	Х	Х	Χ

GENERAL APPLICATIONS:

Agricultural dry fertilizers Air seeder lines Fly ash collection Hvdro excavation Industrial vacuum equipment Material handling - heavy duty abrasive Milling machine scrap recovery Rock, gravel, sand and crushed concrete vacuuming Sewer truck boom hose

TRIPLE RESISTANT LINER

Abrasion Resistant! Water Resistant! Oil Resistant!

Shot blast recovery Slurry handling

CONSTRUCTION:

PVC cover with polyurethane liner and riaid PVC helix.

SERVICE TEMPERATURE:

-40°F (-40°C) to 150°F (+65°C)



Tiger™ "HiTemp" THT™ Series

Wire Reinforced EPDM Wet or Dry Material Handling Hose



AVAILABLE SIZES:

	4"	6"	8"
THT™	Χ	Χ	Χ

GENERAL APPLICATIONS:

Agricultural liquid fertilizer, Fly ash collection, Hydro excavation, Industrial vacuum equipment, Material chutes, Material handling - heavy duty abrasive, Milling machine scrap recovery Rock, gravel, sand and crushed concrete vacuuming, Sewer truck boom hose, Slurry handling

CONSTRUCTION:


EPDM tube and polyethylene helix with steel helical wire.



SERVICE TEMPERATURE:

-40°F (-40°C) to 220°F (+104°C)







Water and Irrigation Hoses

"Blue Water" BW™ Series







ll di di didididididididi

GENERAL APPLICATIONS:

Extreme cold conditions Pumps, rental and construction dewatering Pumps, trash

Water suction – standard duty

CONSTRUCTION:

PVC tube with rigid PVC helix.

SERVICE TEMPERATURE:

-40°F (-40°C) to 150°F (+65°C)

AVAILABLE SIZES:

	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	5"	6"
BW™	Х	Χ	Χ	Х	Χ	Χ	Χ	Χ	Χ	Х

H™/J™/K™ Series **Standard Duty PVC Suction Hose**





GENERAL APPLICATIONS:

Agricultural liquid fertilizer Air seeder lines Drain lines

Irrigation lines

Mining applications (MSHA) Pumps, rental and construction dewatering

Pumps, trash Rock dusting


Water suction - standard duty

CONSTRUCTION:

PVC tube with rigid PVC helix.

-4°F (-20°C) to 150°F (+65°C)







W[™] Series **Heavy Duty PVC Liquid Suction Hose**





GENERAL APPLICATIONS:

Extreme cold conditions (Sizes 4"-16") Fish suction Gold dredging Pumps, rental and construction

dewatering Pumps, trash Slurry handling

Water suction – heavy duty

CONSTRUCTION:

PVC tube with rigid PVC helix.

SERVICE TEMPERATURE:

1"-3": -4°F (-20°C) to 150°F (+65°C) 4"-16": -40°F (-40°C) to 150°F (+65°C)

AVAILABLE SIZES:

								_	_					
	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	5"	6"	8"	10"	12"	14"	16"
WTM	Х	Х	Х	Х	Х	Χ	Х	Х	Χ	Х	Х	Х	Х	Х



Water and Irrigation Hoses

WST-SLR™ Series

Heavy Duty PVC Fabric Reinforced Suction & Discharge Hose with High UV Resistance





GENERAL APPLICATIONS:

Fish suction
Irrigation lines
Pumps, rental and construction
dewatering
Pumps, trash
Suction and discharge
Water suction – heavy duty

CONSTRUCTION:

Double-ply PVC tube, polyester fabric reinforcement and rigid PVC helix.

SERVICE TEMPERATURE:

-4°F (-20°C) to 150°F (+65°C)

AVAILABLE SIZES:

					•	
	1-1/2"	2"	3"	4"	6"	8"
WST-SLR™	Χ	Χ	Χ	Χ	Χ	Х



WST™ Series

Heavy Duty PVC Fabric Reinforced Suction & Discharge Hose



GENERAL APPLICATIONS:

Fish suction
Irrigation lines
Pumps, rental and construction
dewatering
Pumps, trash
Suction and discharge
Water suction – heavy duty

CONSTRUCTION:

Double-ply PVC tube, polyester fabric reinforcement and rigid PVC helix.

SERVICE TEMPERATURE:

-4°F (-20°C) to 150°F (+65°C)

AVAILABLE SIZES:

	1-1/2"	2"	3"	4"	5"	6"	8"
WST™	Х	Χ	Х	Х	Х	Χ	Χ



Cold Flex™ CF™ Series

Extra Heavy Duty Low Temperature PVC Suction Hose



GENERAL APPLICATIONS:

Extreme cold conditions
Irrigation lines
Material handling – standard duty
Pumps, rental and construction
dewatering
Pumps, trash
Slurry handling
Water suction – heavy duty

CONSTRUCTION:

PVC tube with rigid PVC helix.

SERVICE TEMPERATURE:

-40°F (-40°C) to 150°F (+65°C)

AVAILABLE SIZES:

	1-1/2"	2"	2-1/2"	3"	4"	6"	8"
CF TM	Χ	Χ	Х	Χ	Х	Χ	Х



Rubber Water Suction Hose PVC Water Discharge Hose

Industrial Rubber Hose

T202AA - 150 PSI EPDM

General Purpose Water S&D Hose



ALFAGOMMA®

APPLICATIONS:

Suction and delivery of non-corrosive liquids for irrigation, construction, fertilizers and lasso acid solutions

COVER:

Black EPDM - abrasion and ozoneresistant.

REINFORCEMENT:

Spiralled high tensile textile cords with flexible steel helix wire.

TUBE:

Black EPDM.

TEMPERATURE RANGE:

-40°F (-40°C) to 212°F (+100°C)

AVAILABLE SIZES:

	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	3.5"	4"	5"	6"	8"	10"	12"
T202AA	Χ	Х	Χ	Χ	Χ	Χ	Χ	Χ	Χ	Χ	Χ	Χ	Χ

T253AA - 150 PSI EPDM

Layflat Water Discharge Hose





APPLICATIONS:

High pressure, 150 PSI lay flat type hose for general industrial construction and irrigation.

COVER:

Black EPDM – abrasion and ozone-resistant.

REINFORCEMENT:

High tensile textile cords.

TUBE:

Black EPDM.

TEMPERATURE RANGE:

-22°F (-30°C) to 176°F (+80°C)

AVAILABLE SIZES:

	1-1/2"	2"	2-1/2"	3"	4"	6"	6-5/8"	8"	10"	12"
T253AA	Х	Х	Χ	Χ	Χ	Х	Χ	Х	Х	Х

Layflat Hose

Premium PVC Drip Irrigation and Water Discharge Hose



APPLICATIONS:

Drip irrigation, Construction, Industrial, Agricultural

SERVICE TEMPERATURE:

 $-5^{\circ}F(-20^{\circ}C)$ to $170^{\circ}F(+76^{\circ}C)$

Yinylflow[®]

CONSTRUCTION:

Features a balanced polyester yarn spiral wrap, longitudinal strength member and homogeneous PVC tube and cover to prevent separation.

AVAILABLE SIZES:

	1-1/2"	2"	2-1/2"	3"	4"	5"	6"	8"	10"	12"	14"	16"
۷F	Х	Χ	Χ	Χ	Χ	Х	Χ	Χ	Х	Χ	Χ	Х

Layflat Couplings

EZ-Seal™ Leak Resistant Couplings

Ideally suited for layflat hoses

APPLICATIONS:

Agriculture, Chemicals, Petroleum, Construction, Material handling

CONSTRUCTION:

Aluminum; ASTM B85 Grade 380

FEATURES & BENEFITS:

Rubber seals - Help prevent leakage. Versatile - Suitable for use with other PVC and Rubber Hoses.



Pin Lug Hose Shank Couplings - Female Ends



Pin Lug Hose Shank Couplings - Male Ends

Couplings & Accessories



Aluminum Part E Male Adapter x Hose Shank



Aluminum Part C Female Coupler x Hose Shank



Aluminum Part DP Dust Plug



Aluminum Part DC Dust Cap



Kuri-Clamp™ Center Punch Clamps



Heavy Duty T-Bolt Clamps 304 Stainless Steel Band, Bolt and Nut



TigerClamp™ Zinc Plated Carbon Steel Spiral Double Bolt Clamps

(For Counterclockwise Spiral) Specially designed to fit Tigerflex® PVC suction hose. Also works well on rubber suction hose.



Double Bolt Zinc Plated Ductile Iron Hose Clamps



Polypropylene Ball Valves



Stainless Steel Combination Hose Nipples




Pin Lug Hose Shank Couplings



Round Hole Steel Strainer



Polypropylene Strainer



"Ready-To-Go" Stock Length Hose Assemblies



Sewer Cleaning Hoses







2,500 PSI Series - SPOR

A yellow polyolefin tube, single high tensile synthetic fiber braid reinforcement and abrasion resistant orange polyether-urethane cover.







3,000 PSI Series - LLBU, HPBU

A yellow polyolefin tube, double high tensile synthetic fiber braid reinforcement and abrasion resistant blue polyether-urethane cover.



Jetting/Lateral Line Hose







HIGH BURST 4,000 PSI Series - SHBK, LHBK

A yellow seamless thermoplastic tube, double high tensile synthetic fiber braid reinforcement and abrasion resistant black polyether-urethane cover.







4,000 PSI Series - LLGR

A yellow seamless thermoplastic tube, double high tensile synthetic fiber braid reinforcement and abrasion resistant green polyether-urethane cover.







5,000 PSI Series - LLRD

A yellow seamless thermoplastic tube, double high tensile synthetic fiber braid reinforcement and abrasion resistant red polyether-urethane cover.

