



TRUESPRAY™

Agricultural Spray Hoses


Prevents Unwanted Herbicide Carryover Damage!

***Permeation Resistant Inner
Liner for Easy Cleanout!***


***Pin-pricked Cover Vents
Trapped Gases***

Chemical Resistant

New Products!



A4083 Series



A4086 Series



KURIYAMA
OF AMERICA, INC.



EDITION 0318

TRUESPRAY™

Agricultural Spray Hoses

A4083 Series (black)

A4086 Series (blue)

High Pressure Polyethylene Rubber Blend Agricultural Spray Hose

General Applications:

- Agricultural fertilizer, pesticide & herbicide spraying
- Chemical transfer
- Tree spraying

Construction:

Permeation resistant LLDPE/rubber blend tube, two-pass high tensile strength yarn and rubber blend cover.

Service Temperature Range:

-40°F (-40°C) to +130°F (+54°C)

Features and Advantages:

Permeation Resistant Liner! – Special LLDE/rubber blend liner flushes easily with water and resists herbicide and pesticide residue buildup. Helps keep crops free of unwanted chemicals.

High Chemical Resistance – Excellent resistance to most industrial and agricultural chemicals.

Dual Yarn Construction – Results in a highly durable, long-lasting product that can also be used in high pressure applications.

Cold Flex™ Materials – Hose remains flexible in sub-zero temperatures.

Pin-pricked Cover – Vents trapped vapors to help prevent “ballooning”.



Nominal Specifications

Standard Stock Colors		Size Code	Nominal ID		Nominal OD		Max. Working Pressure† (psi)		Standard Lengths Coils (ft)	Approx. Wt. per Pkg. (lbs)
A4083 Black	A4086 Blue		(in)	(mm)	(in)	(mm)	@ 70°F (20°C)	@ 122°F (50°C)		
✓	✓	06	3/8	9.5	0.688	17.5	800	300	300/100	33/11
✓	✓	08	1/2	12.7	0.840	21.3	800	300	300/100	45/15
✓	✓	12	3/4	19.1	1.140	29.0	800	250	300/100	72/24
✓	✓	16	1	25.4	1.400	35.6	400	125	200/100	65/33

† Note: Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.

Note: Use of hydraulic or reusable-type fittings are not recommended for coupling Kuri Tec® hose products. Hose claims involving use of these fittings will be disallowed.

NOTE: For details of the following compliances mentioned above, refer to footnotes listed on page 63 of the Kuri Tec® catalog.

PTHALATE FREE (15), RoHS(16)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.




Prevent Unwanted Herbicide Carryover Damage!

The Kuri Tec® Truespray™ hose has been shown to reduce unwanted herbicide carryover damage from PGR (plant growth-regulating) herbicides such as Dicamba. PGR herbicides, although water soluble, act as weak acids, and their removal requires more time, care and effort (Steckel et al. 2005). In conjunction with proper hose and sprayer cleaning techniques, the Truespray™ hose's permeation resistant liner greatly reduces the amount of PGR herbicide residue buildup compared to other hoses.

Even after repeated flushing other spray hoses can retain significant amounts of herbicide residue buildup long after use. During re-use this buildup can unexpectedly leach out of the hose, causing costly crop damage and subsequent yield loss – even years later! However, the Kuri Tec® Truespray™ hose features a permeation resistant inner liner with superior cleanout characteristics, helping ensure your herbicides and pesticides wind up where you want them, on the field. Scientific studies have shown over a 50% reduction in yield loss associated with herbicide carryover damage compared to other hoses that were studied (Cundiff et al. 2017)*.



Discoloration and cupping of leaves are signs of herbicide damage.



*All performance data was gathered in a controlled environment. Results will vary and may not be representative of the experience of others. Use of the Truespray™ hose is not a replacement for proper cleaning procedures. Please refer to your sprayer manual for proper cleaning procedures.

Steckel L, Chism C, Thompson A (2005) Cleaning Plant Growth Regulator (PGR) Herbicides Out of Field Sprayers. University of Tennessee Agricultural Extension Service W071. 3 p

Cundiff, G., Reynolds, D., & Mueller, T. (2017). Evaluation of Dicamba Persistence among Various Agricultural Hose Types and Cleanout Procedures Using Soybean (Glycine max) as a Bio-Indicator. Weed Science, 65(2), 305-316. doi:10.1017/wsc.2016.29

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

Cautionary Statement

All Products sold and distributed by Kuriyama of America, Inc. are in the nature of commodities and they are sold by published specifications and not for particular purposes, uses or applications. Purchaser shall first determine their suitability for the intended purposes, uses or applications and shall either conduct its own engineering studies or tests, or retain qualified engineers, consultants or testing laboratories and consult with them before determining the proper use, suitability or propriety of the merchandise or Products for the intended purposes, uses or applications.

Kuriyama of America, Inc. ("Seller") does not recommend the Products for any particular purpose, use or application, and the Purchaser or user thereof shall assume full responsibility for the suitability, propriety, use and application of the Products. Purchaser shall follow all instructions contained in Seller's catalogs, brochures, technical bulletins and other documents regarding the Products. The Products, including but not limited to, hose, tubing or couplings, may fail due to the use or conveyance of substances at elevated or lowered temperatures or at excessive pressure, the conveyance of abrasive, injurious, flammable, explosive or damaging substances.

Hose or tubing used in bent configurations will be subjected to increased abrasion. Hose clamps or couplings may loosen after initial installation and all sections of hose and tubing including connections, couplings, clamps, conductivity and bonding should be inspected frequently, regularly and consistently, and should be replaced, adjusted or re-tightened for the avoidance of leakage, for the prevention of injuries or damages, and for general safety purposes. Except as indicated in its Limited Warranty, Seller shall not be liable or responsible for direct or indirect injuries or damages caused by or attributed to the failure or malfunction of any Products sold or distributed by it.

Purchasers or users of the Products should frequently and consistently undertake inspections and protective measures with respect to the use and application of Products, which should include the examination of tube and cover, conditions of the hose or tubing, and the identification, repair or replacement of sections showing cracking, blistering, separations, internal and external abrasions, leaking or slipped couplings or connections and make proper proof tests.

Limited Warranty

The Products sold or distributed by Seller are warranted to its customers to be free from defects in material and workmanship at the time of shipment by us, subject to the following provisions. ALL WARRANTY CLAIMS SHALL BE MADE WITHIN SIX (6) MONTHS AFTER SELLER SHIPPED THE PRODUCTS. SELLER'S LIABILITY HEREUNDER IS LIMITED AT SELLER'S EXCLUSIVE DISCRETION, TO 1) THE PURCHASE PRICE OF ANY PRODUCTS PROVING DEFECTIVE; 2) REPAIR OF ANY DEFECTIVE PRODUCT OR PART THEREOF; OR 3) REPLACEMENT OF ANY DEFECTIVE PRODUCT OR PART UPON ITS AUTHORIZED RETURN TO SELLER.

THIS WARRANTY IS IN LIEU OF AND EXCLUDES ALL OTHER WARRANTIES, EXPRESSED, IMPLIED, STATUTORY, OR OTHERWISE CREATED UNDER APPLICABLE LAW INCLUDING, BUT NOT LIMITED TO, THE WARRANTY OF MERCHANTABILITY AND THE WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL SELLER OR THE MANUFACTURER OF THE PRODUCT BE LIABLE FOR SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING LOSS OF PROFITS, WHETHER OR NOT CAUSED BY OR RESULTING FROM THE NEGLIGENCE OF SELLER AND/OR THE MANUFACTURER OF THE PRODUCT, UNLESS SPECIFICALLY PROVIDED HEREIN. IN ADDITION, THIS WARRANTY SHALL NOT APPLY TO ANY PRODUCTS OR PORTIONS THEREOF WHICH HAVE BEEN SUBJECTED TO ABUSE, MISUSE, IMPROPER INSTALLATION, MAINTENANCE, OR OPERATION, ELECTRICAL FAILURE OR ABNORMAL CONDITIONS, AND TO PRODUCTS WHICH HAVE BEEN TAMPERED WITH, ALTERED, MODIFIED, REPAIRED, REWORKED BY ANYONE NOT APPROVED BY SELLER, OR USED IN ANY MANNER INCONSISTENT WITH THE PROVISIONS OF THE "CAUTIONARY STATEMENT" ABOVE OR ANY INSTRUCTIONS OR SPECIFICATIONS PROVIDED WITH OR FOR THE PRODUCT.

09/17/18 REV

Distributed by:



KURIYAMA
OF AMERICA, INC.

HEADQUARTERS, SALES OFFICE AND WAREHOUSE

360 E. State Parkway, Schaumburg, IL 60173-5335
Phone: (847) 755-0360 • Toll-free Fax: (800) 800-0320
International Fax: (847) 885-0996



kuriyama.com



sales@kuriyama.com



The trademarks contained in this publication are trademarks of Kuriyama of America, Inc.

CONTACT OUR SALES/WAREHOUSE LOCATIONS BELOW WHICH SERVE YOUR AREA

SOUTHWEST WAREHOUSE

KURIYAMA OF AMERICA, INC.

- HOUSTON

200 Portwall Street, Suite 100
HOUSTON, TX 77029
Phone: (713) 674-8212
Toll Free Phone: (800) 501-6808
FAX: (713) 674-5214
Toll Free FAX: (800) 800-5214
E-Mail: sales@kuriyama.com

WESTERN WAREHOUSE

KURIYAMA OF AMERICA, INC.

- SANTA FE SPRINGS

10749 SHOEMAKER AVENUE
SANTA FE SPRINGS, CA 90670-4039
Phone: (562) 941-4507
FAX: (562) 941-8940
Toll-Free FAX: (800) 326-8940
E-Mail: sales@kuriyama.com

SOUTHEAST WAREHOUSE

FORTNEY SALES CO., INC.

4221 Cantrell Road NW
Acworth, GA 30101
Phone: (770) 427-6528
FAX: (770) 423-9249
Toll Free FAX: (800) 423-9249
Web Site: www.fortneysales.com
E-Mail: sales@fortneysales.com

EASTERN WAREHOUSE

EASTERN RUBBER & PLASTICS CO., INC.

100 GOLDMAN DR.
PLUMSTED INDUSTRIAL PARK
CREAM RIDGE, NJ 08514
Phone: (609) 758-0100
FAX: (609) 758-0102
Toll Free FAX: (800) 445-7138
Web Site: www.easternrubber.com
E-Mail: sales@easternrubber.com

IN CANADA:

KURI TEC CORPORATION

140 Roy Boulevard
Brantford, ON, Canada N3R 7K2
Phone: (519) 753-6717
FAX: (519) 753-7737
Web Site: www.kuritec.com
E-Mail: sales@kuritec.com

IN MEXICO:

KURIYAMA DE MÉXICO S DE RL DE CV
AV JOSE PALOMO MARTINEZ NO 520-20 BODEGA 5
PARQUE INDUSTRIAL OMOLAP
APODACA, N.L. CP:66633, MÉXICO
Telefonos: (81) 1086-1870 0 71
Internet: www.kuriyama.com.mx
www.kuriyama.com
Correo Electronico: ventas@kuriyama.com