



Red Fuel Oil Discharge Hose

General Applications:

- A high quality hose to handle oil, diesel, fuel oil and other petroleum products for home delivery. Also suitable for handling regular and unleaded gasolines up to 93 octane.

Construction:

- **Cover** – Red Class A Nitrile/PVC, high oil resistance.
- **Reinforcement** – Spiral polyester yarn with static wire.
- **Tube** – Black Class A Nitrile, high oil resistance.

Service Temperature Range:

-40°F (-40°C) to +212°F (+100°C)

Features and Advantages:

- Long lengths on reels.
- High oil resistance (Class A) rated tube and cover.

Branding:

REDI-TRANSFER FUEL OIL DELIVERY SIZE-WP-MADE IN USA

Packaging:

Cut lengths and bulk reels (maximum 3 pcs. on reel).

Redi-Transfer™ Cut Lengths

Nominal Specifications

Part Number	Color	ID (in)	OD (in)	Working Pressure (psi)	Length (ft)	Weight (lbs/pc)
REDITFR-100x100	RED	1	1.50	250	100	47
REDITFR-100x150	RED	1	1.50	250	150	71
REDITFR-100x200	RED	1	1.50	250	200	94
REDITFR-125x100	RED	1 1/4	1.78	250	100	59
REDITFR-125x125	RED	1 1/4	1.78	250	125	74
REDITFR-125x150	RED	1 1/4	1.78	250	150	89
REDITFR-137x125	RED	1 3/8	1.88	250	125	81
REDITFR-137x150	RED	1 3/8	1.88	250	150	98
REDITFR-150x125	RED	1 1/2	2.09	250	125	100
REDITFR-150x150	RED	1 1/2	2.09	250	150	120
REDITFR-150x175	RED	1 1/2	2.09	250	175	140

Redi-Transfer™ Bulk Hose on Reels

Nominal Specifications

Part Number	Color	ID (in)	OD (in)	Working Pressure (psi)	Reel Length (ft)	Weight (lbs/pc)
REDITFR-100x500	Red	1	1.50	250	500	235
REDITFR-125x450	Red	1 1/4	1.78	250	450	265
REDITFR-137x450	Red	1 3/8	1.88	250	450	293
REDITFR-150x400	Red	1 1/2	2.09	250	400	320

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

