



## *Viper*<sup>®</sup> sti™

## **General Applications:**

- Municipal and industrial fire protection
- Wildland Firefighting

## **Construction:**

- Extruded E-Lite alloy, lightweight and durable.
- Molded rubber teeth.

## **Features and Advantages:**

- Constant gallonage in all positions; straight stream, narrow fog and wide fog settings.
- Raised lug to indicate 30° fog (narrow fog).
- Flush without shutting down nozzle.
- Low expansion foam tube attachment available.
- Twist shutoff to straight stream to fog.

Approvals and Standards – The VIPER<sup>®</sup> STI<sup>™</sup> is National Fire Protection Association (NFPA) 1964 compliant and is manufactured in an ISO 9001 accredited facility. European Standards (EN) 15182-1 and EN15182-2 type 3 Certificates are available by request.

| Nozzle Part<br>Number | Nozzle Model<br>Number | Rigid<br>Inlet<br>(In) | Nozzle Flow |       | Length |      | Weight (each) |      |
|-----------------------|------------------------|------------------------|-------------|-------|--------|------|---------------|------|
|                       |                        |                        | (gpm)       | (lpm) | (in)   | (cm) | (lbs)         | (kg) |
| 1230047               | STI30V NST             | 1                      | 30          | 110   | 5.30   | 13   | 1.17          | 0.53 |
| 1230171               | STI30V NPSH            | 1                      | 30          | 110   | 5.30   | 13   | 1.17          | 0.53 |

