

Viper® VTE™

General Applications:

- · General plant wash-down service
- Dust control
- Wildland firefighting

Construction:

- Composite housing with brass stem and rubber bumper.
- Female NST or NPSH threads.
- Fixed teeth.
- Available in Red or Black colors.

Features and Advantages:

- Adjustable Flow Control Twisting nozzle adjusts spray pattern from full stream to misting fog.
- Impact Resistant Rubber bumpers protect nozzle from damage if dropped or dragged.
- **Lightweight** Compact design reduces worker fatigue.

Approvals and Standards – The VIPER® VTE™ is National Fire Protection Association (NFPA) 1964 compliant and is manufactured in an ISO 9001 accredited facility. European Standards (EN) 15182-1 and EN15182-2 type 3 Certificates are available by request.

Nozzle Part Number	Nozzle Model Number	Rigid Inlet (In)	Color	Nozzle Flow		Length		Weight (each)	
				(gpm)	(lpm)	(in)	(cm)	(lbs)	(kg)
I150006C	VTE-1550	1 NST	Red	30	125	5.30	13	0.44	0.20
I150004C	VTE-1550	1 NPSH	Red	30	125	5.30	13	0.44	0.20
I150005C	VTE-1550	1 NST	Black	30	125	5.30	13	0.44	0.20
I150034	VTE-2510	1 1/2 NST	Red	95	360	5.90	15	0.66	0.30
1218950	VTE-2510	1 1/2 NPSH	Red	95	360	5.90	15	0.66	0.30
I150015	VTE-2510	1 1/2 NST	Black	95	360	5.90	15	0.66	0.30